



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION								
Product:	Air-Shield™ Flashing Tape	Part Number: 5114000						
Manufacturer:	W. R. Meadows®, Inc.	Address: 300 Industrial Drive Hampshire, Illinois 60140						
Telephone:	(847) 214-2100	In case of emergency, dial (800) 424-9300 (CHEMTREC)						
Revision Date:	8/31/2018							
Product Use:	Flexible Flashing Tape							
SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS								
HMIS								
 Health 	0	Product is classified as non-hazardous per OSHA 1910.1200. Air-Shield Flashing Tape						
 Flammability 	1	is defined by OSHA as an "article." A manufactured item that is formed to a specific						
 Reactivity 	0	shape or design during manufacture that does not release or result in exposure to a						
 Personal Protection 		hazardous chemical under normal use conditions.						
SECTION 3: HAZARDS COMPONENTS								
		% by	SARA	Vapor Pressure	LEL			
Chemical Name:	CAS Number	Weight	313	(mm Hg@20°C)	(@24°C)			
1. Petroleum Asphalt	8052-42-4	50-80	No	N/A	N/A	N/A = Not Applicable		
Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."								
SECTION 4: EMERGENCY AND FIRST AID PROCEDURES								
EYE CONTACT: Not expected to be an exposure route.								
SKIN CONTACT: Wash affected areas with soap and water if available								
INHALATION: Not expected to be an exposure route.								
INGESTION: Not expected to be an exposure source.								
MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC: See Section Eleven for Symptoms/Effects.								
SECTION 5: FIRE AND EXPLOSIVES HAZARDS								
FLASHPOINT: Not Applicable; Product is a solid.								
EXTINGUISHING MEDIA: Water fog, foam, dry chemical.								
CHEMICAL/COMBUSTION HAZARDS: Oxides and compounds of nitrogen/sulfur.								
PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Avoid smoke inhalation. Use appropriate respiratory protection.								
SECTION 6: ACCIDENTAL RELEASE MEASURES								
SPILL OR LEAK PROCEDURES: Not applicable. Product is a solid.								
SECTION 7: HANDLING AND STORAGE								
SAFE HANDLING PROCEDURES: Avoid direct contact.								
SAFE STORAGE: Prevent job-site damage.								
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION								
		OSHA			ACGIH			
Chemical Name:	PEL	PEL/CEILING	PEL/STEL	SKIN	TLV	TLV/CEILING	TLV/STEL	SKIN
1. Petroleum Asphalt	5 mg/m ³ *	N/E	N/E	No	0.5 mg/m ³ *	N/E	N/E	N/E
ENGINEERING CONTROLS: None required under normal use conditions.					N/E = Not Established		*: Asphalt Fumes	
PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, chemical-resistant gloves.								
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES								
BOILING POINT: N/A	VAPOR DENSITY: N/A			% VOLATILE BY VOLUME: N/A				
EVAPORATION RATE: N/A	pH LEVEL: N/A			% VOLATILE BY WEIGHT: N/A				
WEIGHT PER GALLON: N/A	PRODUCT APPEARANCE: Black Solid			VOC CONTENT: N/A				
ODOR: None	ODOR THRESHOLD: N/D			MELTING/FREEZING POINT: N/D				
FLASH POINT: See Section 5	FLAMMABILITY: N/D			UEL/LEL: N/D				
VAPOR PRESSURE: N/D	RELATIVE DENSITY: N/D			SOLUBILITY: N/D				
PARTITION COEFFICIENT: N/D	AUTOIGNITION TEMPERATURE: N/D			DECOMPOSITION TEMPERATURE: N/D				
VISCOSITY: N/D	N/D: Not Determined							

